

## THE CONTINUOUS INKJET PRINTER FOR EXTRUSION

Dedicated to the pipe, cable, tube and profile industries, the 9450 E combines a premium ink circuit with a next generation printhead design that will ensure the quality of your codes even on dark substrates with an optimized TCO.

## Optimize your operating time and expenses

- Up to 3,000\* km of cable printing  
Without printhead cleaning.
- Reduced TCO\*\*  
20% ink savings without compromising on contrast.
- Reduced additive consumption  
Only 3 ml/h at 20 °C.
- High speed  
Up to 1,000 m/min for wire harnessing applications.
- Smart consumable system  
No set-up required.
- Mistake-proof user interface (UI)  
Even when entering long messages.



## Precision all the way, every time

- Precise, even on the tiniest of wires  
Can code wires as small as 1mm character height.
- Precise when using the embedded metering function  
2 mm tolerance.
- Precise at start-up  
Its automatic cleaning system, coupled with Jet Speed control technology, provides clean, hassle-free start-ups and high quality codes, every time.
- Precise after maintenance  
Its modular **Intelli'Swap** design, with an extrusion-dedicated bracket which can be repositioned single-handed in one second, makes maintenance easy.



Extrusion-dedicated UI: metering, interleaving of 2 messages, quick access to counter setting, tolerance optimization, etc.

## Specialty inks for contrasted and durable codes

- Premium inks designed for rough environmental conditions  
Part of our **Intelli'Link** system, they are fast drying and non-migrating with resistance to UV, automotive fluids, underwater environments, vulcanization, etc.
- Long-lasting codes, even on PE  
Through dedicated inks specially formulated and tested for high contrast and perfect adhesion on a wide variety of surfaces, including the most difficult ones (PVC, PE, LSZH, PP, etc.).
- Multiple colors  
Black, white, orange, blue, green, red and yellow as well as a one-ink-fits-all silver.
- MEK-free options  
A wide array of inks (including a white one) which reduce VOC emissions and enhance employee safety, while simplifying paperwork, particularly when exporting.



Choose from a wide range of inks or streamline logistics and costs with the one-ink-fits-all silver.

# 9450 E - Specifications

## Print features

- Mono-jet printhead
- G head (printing resolution: 71 dpi) or M head (printing resolution: 115 dpi)
- Up to 5 lines of print
- Print speed: up to 1,000 m/min
- Font height from 5 to 32 dots
- Character height: from 1 to 11 mm
- Wide choice of 1D and 2D barcodes: EAN8/EAN13/GS1-128/U PCA/U PCE barcodes, code 39, code 128, interleaved 2 of 5, Datamatrix, QR code
- Wide choice of characters: Latin, Arabic, Cyrillic, Hebrew, Japanese, Chinese, Korean etc.

## PC software

- Compatible with CoLOS® Base, CoLOS Line and CoLOS Factory
- Logo creation with CoLOS Graphics
- OEM protocol compatibility: Komax, Schleuniger etc.

## Operations

- Message library (up to 1,000 messages) International operator/machine interface with a wide choice of languages
- WYSIWYG 7-inch wide touch screen: real-time display of remaining print capacity expressed in hours and number of messages; integrated assistance and alert system; simplified message printing and management; creation of user profiles; tracking of consumption and printer availability
- Additional functionalities: metering, interleaving of 2 messages, on-the-fly production changes, quick access to counter setting, optimization of tolerance control, chimney characters, DIN mode
- USB and SD ports
- Jet Speed Control guarantees marking quality
- Automatic selection of fonts, depending on print speed and printhead/object distance
- Premium ink circuit to run all types of inks
- Intelli'Ink system: broad range of multi-use, high-performance or high-contrast inks, including MEK-free option
- Sealed 0.8-liter cartridges with foolproofing system
- Intelli'Swap design for quick connect/disconnect of accessories (photocell, alarm, encoder, bracket)
- Parent/child connectivity
- Ethernet connectivity
- Specific date management (rounding date function)

## Other characteristics

- Weight: 25 kg
- Table-top or vertical mounting
- Ultra-flexible 3-meter umbilical cable
- Stainless steel cabinet and printhead case
- Dust/humidity protection rating: IP56 not requiring plant air
- Operating temperature range: 0 to 45 °C depending on printer model and ink used
- Humidity: 10 to 90% non-condensing
- Electrical power supply: 100-120 V or 200-240 V with automatic switching; frequency 50/60 Hz; power 60 VA

## Options

- Printhead pressurization kit
- IP66 protection (requires plant air)
- 9450 Ec for pigmented ink use
- Enhanced autonomy kit
- RS-232/422 connectivity, parallel interface, many I/O possibilities to enable remote operation
- Ultra-flexible 6-meter umbilical cable

## Accessories


- Printer supports: stands (stainless steel or aluminum), table or wall mounting brackets
- Printhead stand (stainless steel) and different, quick fit printhead brackets (single-handed repositioning in 1 second)
- Photocells; encoders; alarm beacons (24 V)




## Printhead

Minimum radius of curvature of the umbilical:

- Static: 100 (3.93")
- Dynamic: 150 (5.90")



## Cabinet



We reserve the right to amend the design and/or specifications of our products without notice.  
© 2023 Markem-Imaje, a Dover Company. MARKEM-IMAJE and the MI MARKEM-IMAJE Logo, CoLOS are registered trademarks of Dover Europe Sàrl in the United States, the European Union and various other countries.